

Traditional PVC Hose Range



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
7215P0000	Starter Hose	12.5	15	Braided	3	10	-20 to +40	30
7230P0000	Starter Hose	12.5	30	Braided	3	10	-20 to +40	30
7250P0000	Starter Hose	12.5	50	Braided	3	10	-20 to +40	30



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
7730P0000	Ultraflex Hose	12.5	30	Knitted	5	20	-15 to +60	20
7750P0000	Ultraflex Hose	12.5	50	Knitted	5	20	-15 to +60	20



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
7930P0000	Ultramax Hose	12.5	30	Knitted TNT™	5	25	-15 to +60	25
7950P0000	Ultramax Hose	12.5	50	Knitted TNT™	5	25	-15 to +60	25



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
7830P0000	Ultimate Hose	12.5	30	Knitted TNT™	5	30	-20 to +60	35
7850P0000	Ultimate Hose	12.5	50	Knitted TNT™	5	30	-20 to +60	35

Alternative Hose Range



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
8207	Superhoze	18	7.5	Expanding	2	5*	0 to +40	28
8215	Superhoze	18	15	Expanding	2	5*	0 to +40	28
8230	Superhoze	18	30	Expanding	2	5*	0 to +40	28
8240	Superhoze	18	40	Expanding	2	5*	0 to +40	28



Product Code	Hose Name	Ø (mm)	Length (m)	Technology	Layers	Guarantee	Operating Temperature (°C)	Burst Pressure (Bar)
8125	Tuffhoze	15	25	Hybrid	2	30	-15 to +60	40

Notes:

Alternative hose diameters are based on the internal size and may vary dependant upon water pressure.

Superhoze lengths are up to the value given and are dependent upon water pressure.

It is recommended that all hoses are emptied after use and put away during cold or frosty weather.

*3 year guarantee + additional 2 years if you register online with Hozelock. Terms and conditions apply: www.hozelock.com/guarantee